

# Package ‘fledge’

February 18, 2024

**Title** Smoother Change Tracking and Versioning for R Packages

**Version** 0.1.2

**Date** 2024-02-18

**Description** Streamlines the process of updating changelogs (NEWS.md) and versioning R packages developed in git repositories.

**License** GPL-3

**URL** <https://fledge.cynkra.com/>, <https://github.com/cynkra/fledge>

**BugReports** <https://github.com/cynkra/fledge/issues>

**Imports** brio, cli, desc ( $\geq 1.2.0$ ), gert ( $\geq 1.4.0$ ), purrr ( $\geq 0.3.2$ ), rematch2, rlang ( $\geq 0.4.12$ ), tibble, usethis ( $\geq 1.5.0$ ), whoami, withr

**Suggests** mockery, covr, fansi, fs, knitr, parsedate, rmarkdown, rstudioapi, testthat ( $\geq 3.0.0$ ), callr, pkgload

**VignetteBuilder** knitr

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Kirill Müller [aut, cre, cph] (<https://orcid.org/0000-0002-1416-3412>), Patrick Schratz [aut] (<https://orcid.org/0000-0003-0748-6624>), Maëlle Salmon [ctb] (<https://orcid.org/0000-0002-2815-0399>)

**Maintainer** Kirill Müller <[kirill@cynkra.com](mailto:kirill@cynkra.com)>

**Repository** CRAN

**Date/Publication** 2024-02-18 16:30:02 UTC

## R topics documented:

bump_version . . . . .	2
commit_version . . . . .	3

create_demo_project . . . . .	4
finalize_version . . . . .	4
get_last_tag . . . . .	5
get_top_level_commits . . . . .	6
tag_version . . . . .	7
unbump_version . . . . .	8
update_news . . . . .	9
update_version . . . . .	10
with_demo_project . . . . .	11

<b>Index</b>	<b>12</b>
--------------	-----------

---

bump_version	<i>Bump package version</i>
--------------	-----------------------------

---

## Description

Calls the following functions:

1. Verify that the current branch is the main branch.
2. [update\\_news\(\)](#)
3. [update\\_version\(\)](#), using the which argument
4. Depending on the which argument:
  - If "dev", [finalize\\_version\(\)](#) with push = FALSE
  - Otherwise, [commit\\_version\(\)](#).

## Usage

```
bump_version(which = "dev")
```

## Arguments

which	Component of the version number to update. Supported values are "dev" (default), "patch", "minor" and "major".
-------	--

## Value

None

## Bumped too soon?

Have you just run [bump\\_version\(\)](#), then realized "oh shoot, I forgot to merge that PR"? Fear not, run [unbump\\_version\(\)](#), merge that PR, run [bump\\_version\(\)](#).

## See Also

[unbump\\_version\(\)](#)

**Examples**

```
# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
})
```

---

 commit\_version

*Commits NEWS.md and DESCRIPTION to Git*


---

**Description**

Commits changes to NEWS.md and DESCRIPTION, amending a previous commit created by **fledge** if necessary.

**Usage**

```
commit_version()
```

**Value**

Invisibly: TRUE if a previous commit for that version has been amended, FALSE if not.

**Examples**

```
# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
  desc::desc_add_author(given = "Jane", family = "Doe", role = "ctb")
  fledge::commit_version()
})
```

---

create\_demo\_project     *Create example repo for fledge demos*

---

### Description

Create example repo for fledge demos

### Usage

```
create_demo_project(  
  open = rlang::is_interactive(),  
  name = "tea",  
  maintainer = NULL,  
  email = NULL,  
  date = "2021-09-27",  
  dir = file.path(tempdir(), "fledge"),  
  news = FALSE  
)
```

### Arguments

open	Whether to open the new project.
name	Package name.
maintainer	Name for DESCRIPTION and git.
email	Email for DESCRIPTION and git.
date	String of time for DESCRIPTION and git.
dir	Directory within which to create the mock package folder.
news	If TRUE, create a NEWS.md file.

### Value

The path to the newly created mock package.

---

finalize\_version     *Finalize package version*

---

### Description

Calls the following functions:

1. `commit_version()`
2. `tag_version()`, setting `force = TRUE` if and only if `commit_version()` amended a commit.
3. Force-pushes the created tag to the "origin" remote, if `push = TRUE`.

**Usage**

```
finalize_version(push = FALSE)
```

**Arguments**

push                    If TRUE, push the created tag.

**Value**

None

**Examples**

```
# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
  # Edit news by hand
  # ...
  # Once done
  fledge::finalize_version()
})
```

---

get\_last\_tag

*The most recent tag*

---

**Description**

Returns the most recent Git tag.

**Usage**

```
get_last_tag()
```

**Value**

A one-row tibble with columns `name`, `ref` and `commit`. For annotated tags (as created by `fledge`), `commit` may be different from the SHA of the commit that this tag points to. Use `gert::git_log()` to find the actual commit.

**Examples**

```

# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
  fledge::finalize_version()
  print(get_top_level_commits(since = NULL))
  print(fledge::get_last_tag())
})

```

---

get\_top\_level\_commits *All top-level commits*

---

**Description**

Return all top-level commits since a particular version as commit objects.

**Usage**

```
get_top_level_commits(since = NULL)
```

**Arguments**

`since` A commit SHA, e.g. as returned from [get\\_last\\_tag\(\)](#). If NULL, the entire log is retrieved.

**Value**

A [tibble](#) with at least two columns:

- `commit`: the commit SHA
- `message`: the commit message

**Examples**

```

# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)

```

```

# Add a new R file.
usethis::use_r("cool-function", open = FALSE)
# Pretend we added useful code inside it.
# Track the new R file with Git.
gert::git_add("R/cool-function.R")
gert::git_commit("- Add cool function.")
# Bump version with fledge.
fledge::bump_version()
fledge::finalize_version()
print(get_top_level_commits(since = NULL))
print(fledge::get_last_tag())
})

```

tag\_version

*Create a new version tag***Description**

Parses NEWS.md and creates/updates the tag for the most recent version.

**Usage**

```
tag_version(force = FALSE)
```

**Arguments**

**force** Re-tag even if the last commit wasn't created by `bump_version()`. Useful when defining a CRAN release.

**Value**

The created tag, invisibly.

None

**Examples**

```

# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()

```

```
fledge::update_news(c("- something I forgot", "- blabla"))
fledge::update_version()
gert::git_add("NEWS.md")
gert::git_commit(message = "release notes tweaking")
fledge::tag_version()
print(fledge::get_last_tag())
})
```

---

unbump_version	<i>Undoes bumping the package version</i>
----------------	---

---

### Description

This undoes the effect of a `bump_version()` call, with a safety check.

### Usage

```
unbump_version()
```

### Value

NULL, invisibly. This function is called for its side effects.

None

### See Also

`bump_version`

### Examples

```
# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
  # Oh no, we forgot to also add the awesome function for that version!
  # UNBUMP
  fledge::unbump_version()
  # Add a new R file.
  usethis::use_r("awesome-function", open = FALSE)
  # Pretend we added awesome code inside it.
```



```

# Track the new R file with Git.
gert::git_add("R/awesome-function.R")
gert::git_commit("- Add awesome function.")
# Bump version with fledge.
fledge::bump_version()
#'
})

```

---

update\_news

*Update NEWS.md with messages from top-level commits*


---

## Description

Lists all commits from a range (default: top-level commits since the most recent tag) and adds bullets from their body to NEWS.md. Creates NEWS.md if necessary.

## Usage

```
update_news(messages = NULL)
```

## Arguments

messages	A character vector of commit messages, e.g. as in the message column in the return value of <code>get_top_level_commits()</code> . The default uses the top level commits since the last tag as retrieved by <code>get_last_tag()</code> .
----------	--

## Value

None

## Examples

```

# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
  fledge::update_news(c("- something I forgot", "- blabla"))
  fledge::update_version()
  gert::git_add("NEWS.md")
  gert::git_commit(message = "release notes tweaking")
  fledge::tag_version()
})

```

```
print(fledge::get_last_tag())
})
```

---

update_version	<i>Update NEWS.md and DESCRIPTION with a new version</i>
----------------	--

---

### Description

Bumps a version component and adds to NEWS.md and DESCRIPTION.

### Usage

```
update_version(which = "dev")
```

### Arguments

which	Component of the version number to update. Supported values are "dev" (default), "patch", "minor" and "major".
-------	--

### Value

None

### Examples

```
# Create mock package in a temporary directory.
# Set open to TRUE if you want to play in the mock package.
with_demo_project({
  # Use functions as if inside the newly created package project.
  # (Or go and actually run code inside the newly created package project!)
  # Add a new R file.
  usethis::use_r("cool-function", open = FALSE)
  # Pretend we added useful code inside it.
  # Track the new R file with Git.
  gert::git_add("R/cool-function.R")
  gert::git_commit("- Add cool function.")
  # Bump version with fledge.
  fledge::bump_version()
  fledge::update_news(c("- something I forgot", "- blabla"))
  fledge::update_version()
  gert::git_add("NEWS.md")
  gert::git_commit(message = "release notes tweaking")
  fledge::tag_version()
  print(fledge::get_last_tag())
})
```

---

with_demo_project	<i>Run code in temporary project</i>
-------------------	--------------------------------------

---

**Description**

Run code in temporary project

**Usage**

```
with_demo_project(code, dir = NULL, news = TRUE, quiet = FALSE)
```

**Arguments**

code	Code to run with temporary active project
dir	Directory within which to create the mock package folder.
news	If TRUE, create a NEWS.md file.
quiet	Whether to show messages from usethis

**Value**

None

**Examples**

```
with_demo_project({  
  # Add a new R file.  
  usethis::use_r("cool-function", open = FALSE)  
  # Pretend we added useful code inside it.  
  # Track the new R file with Git.  
  gert::git_add("R/cool-function.R")  
  gert::git_commit("- Add cool function.")  
  # Bump version with fledge.  
  fledge::bump_version()  
})
```

# Index

bump\_version, 2  
bump\_version(), 7, 8  
bump\_version\_impl (bump\_version), 2

commit\_version, 3  
commit\_version(), 2, 4  
create\_demo\_project, 4

finalize\_version, 4  
finalize\_version(), 2  
finalize\_version\_impl  
    (finalize\_version), 4

gert::git\_log(), 5  
get\_last\_tag, 5  
get\_last\_tag(), 6, 9  
get\_top\_level\_commits, 6  
get\_top\_level\_commits(), 9

tag\_version, 7  
tag\_version(), 4  
tibble, 6

unbump\_version, 8  
unbump\_version(), 2  
unbump\_version\_impl (unbump\_version), 8  
update\_news, 9  
update\_news(), 2  
update\_version, 10  
update\_version(), 2

with\_demo\_project, 11