

# Package ‘flowchart’

May 30, 2024

**Type** Package

**Title** Tidy Flowchart Generator

**Version** 0.4.0

**Maintainer** Pau Satorra <psatorra@igtp.cat>

**Description** Creates participant flow diagrams directly from a dataframe. Representing the flow of participants through each stage of a study, especially in clinical trials, is essential to assess the generalisability and validity of the results. This package provides a set of functions that can be combined with a pipe operator to create all kinds of flowcharts from a data frame in an easy way.

**License** MIT + file LICENSE

**BugReports** <https://github.com/bruigtp/flowchart/issues>

**Encoding** UTF-8

**LazyData** true

**Imports** Gmisc, grid, tidyr, dplyr, purrr, stringr, tibble, tidyselect, rlang, grDevices

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**Depends** R (>= 4.1.0)

**RoxygenNote** 7.2.3

**URL** <https://bruigtp.github.io/flowchart/>

**NeedsCompilation** no

**Author** Pau Satorra [aut, cre],  
João Carmezim [aut],  
Natàlia Pallarès [aut],  
Cristian Tebé [aut]

**Repository** CRAN

**Date/Publication** 2024-05-30 00:30:03 UTC

## R topics documented:

as_fc . . . . .	2
fc_draw . . . . .	3
fc_export . . . . .	4
fc_filter . . . . .	5
fc_merge . . . . .	7
fc_modify . . . . .	8
fc_split . . . . .	9
fc_stack . . . . .	10
safo . . . . .	11

<b>Index</b>	<b>13</b>
--------------	-----------

---

as_fc	<i>as_fc</i>
-------	--------------

---

### Description

This function allows to initialize a flow chart given any database. It will create a fc object showing the number of rows of the database. If a database is not available, the user can instead directly enter the number of rows in the study.

### Usage

```
as_fc(
  .data = NULL,
  N = NULL,
  label = "Initial dataframe",
  text_pattern = "{label}\n{N}",
  just = "center",
  text_color = "black",
  text_fs = 8,
  bg_fill = "white",
  border_color = "black",
  hide = FALSE
)
```

### Arguments

.data	Data frame to be initialised as a flowchart.
N	Number of rows of the study in case '.data' is NULL.
label	Character with the text that will be shown in the box.
text_pattern	Structure that will have the text in the box. It recognizes label, n, N and perc within brackets. For default it is "{label}\n{N}".
just	Justification for the text: left, center or right. Default is center.
text_color	Color of the text. It is black by default.

text_fs	Font size of the text. It is 8 by default.
bg_fill	Box background color. It is white by default.
border_color	Box border color. It is black by default.
hide	Logical value to hide the initial box or not. Default is FALSE. hide = TRUE can only be combined with fc_split().

### Value

List with the dataset and the initialized flowchart parameters.

### Examples

```
safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_draw()
```

---

fc_draw	<i>fc_draw</i>
---------	----------------

---

### Description

This function allows to draw the flowchart from a fc object.

### Usage

```
fc_draw(
  object,
  arrow_angle = 30,
  arrow_length = grid::unit(0.1, "inches"),
  arrow_ends = "last",
  arrow_type = "closed"
)
```

### Arguments

object	fc object that we want to draw.
arrow_angle	The angle of the arrow head in degrees, as in 'arrow'.
arrow_length	A unit specifying the length of the arrow head (from tip to base), as in 'arrow'.
arrow_ends	One of "last", "first", or "both", indicating which ends of the line to draw arrow heads, as in 'arrow'.
arrow_type	One of "open" or "closed" indicating whether the arrow head should be a closed triangle, as in 'arrow'.

**Value**

Invisibly returns the same object that has been given to the function, with the given arguments to draw the flowchart stored in the attributes.

**Examples**

```
safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(!is.na(group), label = "Randomized", show_exc = TRUE) |>
  fc_split(group) |>
  fc_filter(itt == "Yes", label = "Included in ITT") |>
  fc_filter(pp == "Yes", label = "Included in PP") |>
  fc_draw()
```

---

 fc\_export

*fc\_export*


---

**Description**

This function allows you to export the drawn flowchart to the most popular graphic devices (png, jpeg, tiff, bmp).

**Usage**

```
fc_export(
  object,
  filename,
  path = NULL,
  format = NULL,
  width = NA,
  height = NA,
  units = "px",
  res = 100
)
```

**Arguments**

object	fc object that we want to export.
filename	File name to create on disk.
path	Path of the directory to save plot to: path and filename are combined to create the fully qualified file name. Defaults to the working directory.
format	Name of the graphic device. One of 'png', 'jpeg', 'tiff' or 'bmp'. If NULL (default), the format is guessed based on the filename extension.
width, height	Plot size in units expressed by the 'units' argument. Default is 600px.

units	One of the following units in which the width and height arguments are expressed: "in", "cm", "mm" or "px". Default is "px".
res	The nominal resolution in ppi which will be recorded in the bitmap file, if a positive integer. Also used for units other than the default, and to convert points to pixels. Default is 100.

### Value

Invisibly returns the same object that has been given to the function.

### Examples

```
## Not run:
safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(!is.na(group), label = "Randomized", show_exc = TRUE) |>
  fc_draw() |>
  fc_export("flowchart.png")

#Specifying size and resolution
safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(!is.na(group), label = "Randomized", show_exc = TRUE) |>
  fc_draw() |>
  fc_export("flowchart.png", width = 2500, height = 2000, res = 700)

## End(Not run)
```

---

fc\_filter

*fc\_filter*

---

### Description

This function allows to filter the flowchart in function of a expression that returns a logic value that are defined in terms of the variables in the database. It will generate one box per group showing the number of rows of the group that matches the condition, and will retain only those rows in the data base.

### Usage

```
fc_filter(
  object,
  filter = NULL,
  N = NULL,
  label = NULL,
  text_pattern = "{label}\n {n} ({perc}%)",
  show_exc = FALSE,
```

```

direction_exc = "right",
label_exc = "Excluded",
text_pattern_exc = "{label}\n {n} ({perc}%)",
sel_group = NULL,
round_digits = 2,
just = "center",
text_color = "black",
text_fs = 8,
bg_fill = "white",
border_color = "black",
just_exc = "center",
text_color_exc = "black",
text_fs_exc = 6,
bg_fill_exc = "white",
border_color_exc = "black"
)

```

### Arguments

object	fc object that we want to filter.
filter	Expression that returns a logical value and are defined in terms of the variables in the data frame. The data base will be filtered by this expression, and it will create a box showing the number of rows satisfying this condition.
N	Number of rows after the filter in case 'filter' is NULL.
label	Character that will be the title of the box. By default it will be the evaluated condition.
text_pattern	Structure that will have the text in each of the boxes. It recognizes label, n, N and perc within brackets. For default it is "{label}\n {n} ({perc}%)".
show_exc	Logical value. If TRUE a box showing the number of excluded rows will be added to the flow chart.
direction_exc	One of "left" or "right" indicating if the exclusion box goes into the left direction or in the right direction. By default is "right".
label_exc	Character that will be the title of the added box showing the excluded patients. By default it will show "Excluded".
text_pattern_exc	Structure that will have the text in each of the excluded boxes. It recognizes label, n, N and perc within brackets. For default it is "{label}\n {n} ({perc}%)".
sel_group	Specify if the filtering has to be done only by one of the previous groups. By default is NULL.
round_digits	Number of digits to round percentages. It is 2 by default.
just	Justification for the text: left, center or right. Default is center.
text_color	Color of the text. It is black by default.
text_fs	Font size of the text. It is 8 by default.
bg_fill	Box background color. It is white by default.

<code>border_color</code>	Box border color. It is black by default.
<code>just_exc</code>	Justification for the text of the exclude box: left, center or right. Default is center.
<code>text_color_exc</code>	Color of the text of the exclude box. It is black by default.
<code>text_fs_exc</code>	Font size of the text of the exclude box. It is 6 by default.
<code>bg_fill_exc</code>	Exclude box background color. It is white by default.
<code>border_color_exc</code>	Box background color of the exclude box. It is black by default.

**Value**

List with the filtered dataset and the flowchart parameters with the resulting filtered box.

**Examples**

```
safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(!is.na(group), label = "Randomized", show_exc = TRUE) |>
  fc_draw()
```

---

`fc_merge`

*fc\_merge*

---

**Description**

This function allows to combine horizontally two different flowcharts.

**Usage**

```
fc_merge(fcs)
```

**Arguments**

`fcs` list with all the flowcharts that we want to merge

**Value**

List containing a list with the datasets belonging to each flowchart and another list with each of the flowcharts parameters to merge.

**Examples**

```
# Create first flowchart for ITT
fc1 <- safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(itt == "Yes", label = "Intention to treat (ITT)")

# Create second flowchart for PP
fc2 <- safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(pp == "Yes", label = "Per protocol (PP)")

list(fc1, fc2) |>
  fc_merge() |>
  fc_draw()
```

---

 fc\_modify

*fc\_modify*


---

**Description**

This function allows to modify the ‘\$.fc’ tibble included in each fc object that contains all the parameters of the flowchart.

**Usage**

```
fc_modify(object, fun, ...)
```

**Arguments**

object	flowchart created as a fc object.
fun	A function or formula that will be applied to ‘\$.fc’. If a <code>_function_</code> , it is used as is. If a <code>_formula_</code> , e.g. ‘fun = ~.x  > mutate(x = x + 0.2)’, it is converted to a function.
...	Additional arguments passed on to the mapped function.

**Value**

List with the dataset and the modified flowchart parameters.

**Examples**

```
#Example: let's modify the excluded box
text_exc <- paste0(
  sum(safo$inclusion_crit == "Yes"),
  " not met the inclusion criteria\n",
  sum(safo$exclusion_crit == "Yes"),
```

```

    " met the exclusion criteria"
  )

safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(!is.na(group), label = "Randomized", show_exc = TRUE) |>
  fc_modify(
    ~ . |>
    dplyr::mutate(
      text = ifelse(id == 3, text_exc, text),
      x = ifelse(id == 3, 0.75, x)
    )
  ) |>
  fc_draw()

```

---

 fc\_split

*fc\_split*


---

## Description

This function allows to split the flowchart in function of the categories of a column of the database. It will generate as many boxes as categories has the column showing in each one the frequency of each category. It will additionally group the database per this column.

## Usage

```

fc_split(
  object,
  var = NULL,
  N = NULL,
  label = NULL,
  text_pattern = "{label}\n {n} ({perc}%)",
  sel_group = NULL,
  na.rm = FALSE,
  show_zero = FALSE,
  round_digits = 2,
  just = "center",
  text_color = "black",
  text_fs = 8,
  bg_fill = "white",
  border_color = "black"
)

```

## Arguments

object	fc object that we want to split.
var	variable column of the database from which it will be splitted.
N	Number of rows after the split in case 'var' is NULL.

label	Vector of characters with the label of each category in order. It has to have as many elements as categories has the column. By default, it will put the labels of the categories.
text_pattern	Structure that will have the text in each of the boxes. It recognizes label, n, N and perc within brackets. For default it is "{label}\n {n} ({perc}%)".
sel_group	Specify if the splitting has to be done only by one of the previous groups. By default is NULL.
na.rm	logical. Should missing values of the grouping variable be removed? Default is FALSE.
show_zero	logical. Should the levels of the grouping variable that don't have data be shown? Default is FALSE.
round_digits	Number of digits to round percentages. It is 2 by default.
just	Justification for the text: left, center or right. Default is center.
text_color	Color of the text. It is black by default.
text_fs	Font size of the text. It is 8 by default.
bg_fill	Box background color. It is white by default.
border_color	Box border color. It is black by default.

### Value

List with the dataset grouped by the splitting variable and the flowchart parameters with the resulting split.

### Examples

```
safo |>
  dplyr::filter(!is.na(group)) |>
  as_fc(label = "Randomized patients") |>
  fc_split(group) |>
  fc_draw()
```

---

fc\_stack

*fc\_stack*

---

### Description

This function allows to combine vertically two different flowcharts.

### Usage

```
fc_stack(fcs, unite = FALSE)
```

**Arguments**

`fcs` list with all the flowcharts that we want to merge  
`unite` logical value if the boxes have to be united or not. Default is FALSE.

**Value**

List containing a list with the datasets belonging to each flowchart and the flowchart parameters combining all the flowcharts.

**Examples**

```
# Create first flowchart for ITT
fc1 <- safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(itt == "Yes", label = "Intention to treat (ITT)")

# Create second flowchart for PP
fc2 <- safo |>
  as_fc(label = "Patients assessed for eligibility") |>
  fc_filter(pp == "Yes", label = "Per protocol (PP)")

list(fc1, fc2) |>
  fc_stack() |>
  fc_draw()
```

---

safo

*Random generated dataset from the SAFO study*


---

**Description**

This dataset is a random generated dataset to reproduce the numbers needed to generate the flowchart of the SAFO study. SAFO is an open-label, multicenter, phase III–IV superiority randomized clinical trial to assess whether cloxacillin plus fosfomycin administered for the initial 7-days of therapy achieves better treatment success than cloxacillin alone in hospitalized patients with MSSA bacteremia.

**Usage**

```
data(safo)
```

**Format**

A data frame with 925 rows and 21 columns

**id:** Identifier of each patient. This information does not match the real data.

**inclusion\_crit:** The patient not met the inclusion criteria?

**exclusion\_crit:** The patient met the exclusion criteria?  
**chronic\_heart\_failure:** Exc1: Chronic heart failure?  
**expected\_death\_24h:** Exc2: Clinical status with expected death in <24h?  
**polymicrobial\_bacteremia:** Exc3: Polymicrobial bacteremia?  
**conditions\_affect\_adherence:** Exc4: Conditions expected to affect adherence to the protocol?  
**susp\_prosthetic\_valve\_endocard:** Exc5: Suspicion of prosthetic valve endocarditis?  
**severe\_liver\_cirrhosis:** Exc6: Severe liver cirrhosis?  
**acute\_sars\_cov2:** Exc7: Acute SARS-CoV-2 infection?  
**blactam\_fosfomycin\_hypersens:** Exc8: Beta-lactam or fosfomycin hypersensitivity?  
**other\_clinical\_trial:** Exc9: Participation in another clinical trial?  
**pregnancy\_or\_breastfeeding:** Exc10: Pregnancy or breastfeeding?  
**previous\_participation:** Exc11: Previous participation in the SAFO trial?  
**myasthenia\_gravis:** Exc12: Myasthenia gravis?  
**decline\_part:** The patient declined to participate?  
**group:** Randomized treatment received: cloxacilin alone / cloxacilin plus fosfomycin  
**itt:** The patient belongs to the intention to treat (ITT) group?  
**reason\_itt:** Reason for exclusion from the ITT group.  
**pp:** The patient belongs to the per protocol (PP) group?  
**reason\_pp:** Reason for exclusion from the PP group.

## References

Grillo, S., Pujol, M., Miró, J.M. et al. Cloxacillin plus fosfomycin versus cloxacillin alone for methicillin-susceptible *Staphylococcus aureus* bacteremia: a randomized trial. *Nat Med* 29, 2518–2525 (2023). <https://doi.org/10.1038/s41591-023-02569-0>

# Index

## \* datasets

safo, 11

as\_fc, 2

fc\_draw, 3

fc\_export, 4

fc\_filter, 5

fc\_merge, 7

fc\_modify, 8

fc\_split, 9

fc\_stack, 10

safo, 11