

# Package ‘gfcanalysis’

October 11, 2023

**Version** 1.8.0

**Date** 2023-10-09

**Language** en-us

**Title** Tools for Working with Hansen et al. Global Forest Change Dataset

**Depends** R (>= 3.5.0), raster, methods

**Imports** sf, terra, geosphere, RCurl, plyr, ggplot2, grid, stringr, animation, rasterVis

**Encoding** UTF-8

**Description** Supports analyses using the Global Forest Change dataset released by Hansen et al. gfcanalysis was originally written for the Tropical Ecology Assessment and Monitoring (TEAM) Network. For additional details on the Global Forest Change dataset, see: Hansen, M. et al. 2013. "High-Resolution Global Maps of 21st-Century Forest Cover Change." Science 342 (15 November): 850-53. The forest change data and more information on the product is available at <<http://earthenginepartners.appspot.com>>.

**License** GPL (>= 3)

**URL** <https://github.com/azvoleff/gfcanalysis>

**BugReports** <https://github.com/azvoleff/gfcanalysis/issues>

**LazyData** true

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Alex Zvoleff [aut],  
Matthew Cooper [cre]

**Maintainer** Matthew Cooper <[mw.coop.r@gmail.com](mailto:mw.coop.r@gmail.com)>

**Repository** CRAN

**Date/Publication** 2023-10-11 12:20:02 UTC

## R topics documented:

|                               |           |
|-------------------------------|-----------|
| animate_annual . . . . .      | 2         |
| annual_stack . . . . .        | 3         |
| calc_gfc_tiles . . . . .      | 4         |
| calc_pixel_areas . . . . .    | 5         |
| check_aoi . . . . .           | 5         |
| download_tiles . . . . .      | 6         |
| extract_gfc . . . . .         | 7         |
| gfc_stats . . . . .           | 8         |
| gfc_tiles . . . . .           | 9         |
| plot_gfc . . . . .            | 9         |
| scale_by_pixel_area . . . . . | 10        |
| scale_toar . . . . .          | 10        |
| test_poly . . . . .           | 11        |
| threshold_gfc . . . . .       | 11        |
| utm_zone . . . . .            | 13        |
| <b>Index</b>                  | <b>15</b> |

---

|                |   |
|----------------|---|
| animate_annual | <i>Plot an animation of forest change within a given area of interest (AOI)</i> |
|----------------|---|

---

### Description

Produces an animation of annual forest change in the area bounded by the extent of a given AOI, or AOIs. The AOI polygon(s) is(are) also plotted on the image. The `gfc_stack` must be pre-calculated using the `annual_stack` function. The animation can be either an animated GIF (if `type` is set to `'gif'`) or a series of `'.png'` files with a corresponding `'.html'` webpage showing a simple viewer and the forest change animation (if `type` is set to `'html'`). The HTML option is recommended as it requires no additional software to produce it. The animated GIF option will only work if the `imagemagick` software package is installed beforehand (this is done outside of R).

### Usage

```
animate_annual(
  aoi,
  gfc_stack,
  out_dir = getwd(),
  out_basename = "gfc_animation",
  site_name = "",
  type = "html",
  height = 3,
  width = 3,
  dpi = 300,
  dataset = "GFC-2022-v1.10"
)
```

**Arguments**

|              |  |
|--------------|--|
| aoi          | one or more AOI polygons as a SpatialPolygonsDataFrame or sf object. If there is a 'label' field in the dataframe, it will be used to label the polygons in the plots. If the AOI is not in the WGS84 geographic coordinate system, it will be reprojected to WGS84. |
| gfc_stack    | a GFC product subset as a RasterStack (as output by <a href="#">annual_stack</a> )   |
| out_dir      | folder for animation output  |
| out_basename | basename to use when naming animation files  |
| site_name    | name of the site (used in making title)  |
| type         | type of animation to make. Can be either "gif" or "html"   |
| height       | desired height of the animation GIF in inches  |
| width        | desired width of the animation GIF in inches   |
| dpi          | dots per inch for the output image   |
| dataset      | which version of the Hansen data to use <a href="#">annual_stack</a> was run   |

**See Also**

[annual\\_stack](#)

---

annual\_stack

*Generate an annual stack of forest change from GFC product*

---

**Description**

Uses thresholded GFC data as output by [threshold\\_gfc](#) to make an annualized layer stack of forest change. See Details for the class codes used in the annual raster stack. The [animate\\_annual](#) function can be used to produce an animation of forest change from the generated layer stack.

**Usage**

```
annual_stack(gfc, dataset = "GFC-2022-v1.10")
```

**Arguments**

|         |   |
|---------|---|
| gfc     | thresholded extract of GFC product for a given AOI (see <a href="#">threshold_gfc</a> ) |
| dataset | which version of the Hansen data to use   |

## Details

The output raster stack uses the following codes to describe forest change at each pixel:

|                      |   |
|----------------------|---|
| Nodata               | 0 |
| Forest               | 1 |
| Non-forest           | 2 |
| Forest loss          | 3 |
| Forest gain          | 4 |
| Forest loss and gain | 5 |
| Water                | 6 |

## See Also

[threshold\\_gfc](#), [animate\\_annual](#)

---

calc\_gfc\_tiles

*Calculate the GFC product tiles needed for a given AOI*

---

## Description

Intersects an AOI with the GFC product grid to determine what tiles are need to cover the AOI.

## Usage

```
calc_gfc_tiles(aoi)
```

## Arguments

**aoi** an Area of Interest (AOI) as a `SpatialPolygons*` or `sf` object. If the AOI is not in the WGS84 geographic coordinate system, it will be reprojected to WGS84.

## Value

a `sf` of the GFC tiles needed to cover the AOI

## Examples

```
tiles <- calc_gfc_tiles(test_poly)
plot(tiles)
plot(test_poly, lt=2, add=TRUE)
```

---

|                  |  |
|------------------|--|
| calc_pixel_areas | <i>Calculates the pixel area for each line of a raster</i> |
|------------------|--|

---

**Description**

Calculates the pixel area for each line of a raster

**Usage**

```
calc_pixel_areas(x)
```

**Arguments**

x                    a Raster\* object

**Value**

a vector with the area in square meters of the pixels in each line of x (vector has length equal to nrow(x))

---

|           |  |
|-----------|--|
| check_aoi | <i>Check if aoi is an sf or sp type object If sp, convert to sf and return</i> |
|-----------|--|

---

**Description**

Check if aoi is an sf or sp type object If sp, convert to sf and return

**Usage**

```
check_aoi(aoi)
```

**Arguments**

aoi                    the area of interest object

---

|                |                                    |
|----------------|------------------------------------|
| download_tiles | <i>Download a set of GFC tiles</i> |
|----------------|------------------------------------|

---

### Description

This function first checks whether each tile in a set GFC product tiles is present locally, and that local file sizes match the file sizes of the files available on the Google server hosting the GFC product. Next, the function downloads all tiles that either are not present locally, or that are present but have file sizes differing from the file on the Google server.

### Usage

```
download_tiles(  
  tiles,  
  output_folder,  
  images = c("treecover2000", "lossyear", "gain", "datamask"),  
  dataset = "GFC-2022-v1.10"  
)
```

### Arguments

|               |   |
|---------------|---|
| tiles         | sf with GFC product tiles to download, as calculated by the <code>calc_gfc_tiles</code> function.                     |
| output_folder | the folder to save output data in   |
| images        | which images to download. Can be any of 'treecover2000', 'loss', 'gain', 'lossyear', 'datamask', 'first', and 'last'. |
| dataset       | which version of the Hansen data to use   |

### See Also

[extract\\_gfc](#)

### Examples

```
## Not run:  
output_folder <- 'H:/Data/TEAM/GFC_Product'  
tiles <- calc_gfc_tiles(test_poly)  
download_tiles(tiles, output_folder)  
  
## End(Not run)
```

---

|             |  |
|-------------|--|
| extract_gfc | <i>Extracts GFC data for a given AOI</i> |
|-------------|--|

---

### Description

This function extracts a dataset for a given AOI from a series of pre-downloaded GFC tiles. The [download\\_tiles](#) function should be used beforehand in order to download the necessary data to the specified data\_folder. Note that the output file format is fixed as GeoTIFF with LZW compression.

### Usage

```
extract_gfc(  
  aoi,  
  data_folder,  
  to_UTM = FALSE,  
  stack = "change",  
  dataset = "GFC-2022-v1.10",  
  ...  
)
```

### Arguments

|             |  |
|-------------|--|
| aoi         | an Area of Interest (AOI) as a sf object. If the AOI is not in WGS 1984 (EPSG:4326), it will be reprojected to WGS84.                      |
| data_folder | folder where downloaded GFC product tiles are located (see <a href="#">download_tiles</a> function).                                       |
| to_UTM      | if TRUE, then reproject the output into the UTM zone of the AOI centroid. If FALSE, retain the original WGS84 projection of the GFC tiles. |
| stack       | the layers to extract from the GFC product. Defaults to "change". See Details.   |
| dataset     | which version of the Hansen data to use  |
| ...         | additional arguments as for <a href="#">writeRaster</a> , such as filename, or overwrite.  |

### Details

The stack option can be "change" (the default), "first", or "last". When set to "change", the forest change layers (treecover2000, loss, gain, lossyear, and datamask) will be extracted for the given aoi. The "first" and "last" options will mosaic the 2000 or last year composite top of atmosphere (TOA) reflectance images (respectively).

### Value

RasterStack with GFC layers

### See Also

[download\\_tiles](#), [annual\\_stack](#), [gfc\\_stats](#)

---

`gfc_stats`*Produce a table of forest cover change statistics for a given AOI*

---

### Description

For a given AOI, this function produces two tables: an annual forest loss table (in hectares, by default), and a table specifying 1) the total area of pixels that experienced forest gain and, 2) the total area of pixels that experienced both loss and gain over the full period (from 2000 through the end date of the specific product you are using, depending on the chosen dataset). Note that forest gain and combined loss and gain are not available in the GFC product on an annualized basis. Use [extract\\_gfc](#) to extract the GFC data for the AOI, and threshold it using [threshold\\_gfc](#) prior to running this function.

### Usage

```
gfc_stats(aoi, gfc, scale_factor = 1e-04, dataset = "GFC-2022-v1.10")
```

### Arguments

|                           |  |
|---------------------------|--|
| <code>aoi</code>          | one or more Area of Interest (AOI) polygon(s) as a <code>SpatialPolygons*</code> . See Details.                          |
| <code>gfc</code>          | extract of GFC product for a given AOI (see <a href="#">extract_gfc</a> ), recoded using <a href="#">threshold_gfc</a> . |
| <code>scale_factor</code> | how to scale the output data (from meters). Defaults to .0001 for output in hectares.                                    |
| <code>dataset</code>      | which version of the Hansen data to use  |

### Details

If the `aoi` object is not in the coordinate system of `gfc`, it will be reprojected. If there is a "label" attribute, it will be used to label the output statistics. Otherwise, unique names ("AOI 1", "AOI 2", etc.) will be generated and used to label the output. If multiple AOIs share the same labels, statistics will be provided for the union of these AOIs.

### Value

list with two elements "loss\_table", a `data.frame` with statistics on forest loss, and "gain\_table", with the area of forest gain, and area that experienced both loss and gain. The units of the output are hectares (when `scale_factor` is set to .0001).

### See Also

[extract\\_gfc](#), [threshold\\_gfc](#)



---

|           |   |
|-----------|---|
| gfc_tiles | <i>Grid of tiles used for the GFC product</i> |
|-----------|---|

---

**Description**

Contains a `SpatialPolygonsDataFrame` with a 10 x 10 degree grid in WGS84 coordinate system, covering the area from 180W-180E and 80N-60S, the tile system used by the GFC Product.

---

|          |   |
|----------|---|
| plot_gfc | <i>Plot forest change (relative to 2000) for a given year</i> |
|----------|---|

---

**Description**

Plots a single layer of forest change from a layer stack output by [annual\\_stack](#).

**Usage**

```
plot_gfc(fchg, aoi, title_string = "", size_scale = 1, maxpixels = 50000)
```

**Arguments**

|              |  |
|--------------|--|
| fchg         | a forest change raster layer (a single layer of the layer stack output by <a href="#">annual_stack</a> )   |
| aoi          | one or more AOI polygons as a <code>SpatialPolygonsDataFrame</code> or <code>sf</code> object. If there is a 'label' field in the dataframe, it will be used to label the polygons in the plots. If the AOI is not in WGS 1984 (EPSG:4326), it will be reprojected to WGS84. |
| title_string | the plot title   |
| size_scale   | a number used to scale the size of the plot text   |
| maxpixels    | the maximum number of pixels from fchg to use in plotting  |

**See Also**

[annual\\_stack](#), [animate\\_annual](#)

---

scale\_by\_pixel\_area     *Scales a raster by the area of each pixel in meters*

---

### Description

Calculates the area (in meters) of each pixel in a raster, scales the value of each pixel by the area, applies the desired scale factor, and returns the result as a RasterLayer. Useful for calculating class areas based on a classified raster in a geographic coordinate system. Assumes that raster is not rotated (latitudes of every pixel in a given row are identical). Processes block by block to support handling very large rasters.

### Usage

```
scale_by_pixel_area(
  x,
  filename,
  datatype,
  pixel_areas = NULL,
  scale_factor = 1
)
```

### Arguments

|              |   |
|--------------|---|
| x            | a Raster* object  |
| filename     | (optional) filename for output raster   |
| datatype     | (optional) datatype for output raster see <a href="#">dataType</a> NOT YET SUPPORTED  |
| pixel_areas  | a vector giving the area of each cell in a single column of the raster. See <a href="#">calc_pixel_areas</a> . If NULL, this vector will be calculated based on the coordinate system of x. |
| scale_factor | a value to scale the results by   |

### Value

RasterLayer with pixel areas (in meters)

---

scale\_toar     *Scale the first or last top of atmosphere (TOA) reflectance images*

---

### Description

This function applies the scale factors provided by Hansen et al. to rescale the first and last TOA reflectance images from integer to floating point. The following scale factors are used: band 3, 508; band 4, 254; band 5, 363; band 7, 423. The output datatype is FLT4S.

**Usage**

```
scale_toar(x, ...)
```

**Arguments**

x the "first" or "last" image for a given aoi as a RasterStack (see stack option for [extract\\_gfc](#)).

... additional arguments as for [writeRaster](#), such as filename, or overwrite.

**Value**

RasterStack of TOA reflectance values

**See Also**

[extract\\_gfc](#)

---

test\_poly

*Polygon outlining TEAM site in Caxiuanã, Brazil*

---

**Description**

Contains a SpatialPolygonsDataFrame with a simplified polygon of the area within the Tropical Ecology Assessment and Monitoring (TEAM) network site in Caxiuanã, Brazil.

---

threshold\_gfc

*Threshold the GFC product*

---

**Description**

Uses the GFC data output from [extract\\_gfc](#) to make an thresholded layer stack with five layers: treecover2000, loss, gain, lossyear, and datamask layers. See Details for the coding used in each layer. Note that the output file format is fixed as GeoTIFF with LZW compression.

**Usage**

```
threshold_gfc(gfc, forest_threshold = 25, ...)
```

**Arguments**

gfc extract of GFC product for a given AOI (see [extract\\_gfc](#))

forest\_threshold percent woody vegetation to use as a threshold for mapping forest/non-forest

... additional arguments as for [writeRaster](#), such as filename or overwrite

**Details**

The output uses the following codes to describe forest change at each pixel:

**Band 1 (forest2000)**

|            |   |
|------------|---|
| Non-forest | 0 |
| Forest     | 1 |

**Band 2 (lossyear)**

|              |    |
|--------------|----|
| No loss      | 0  |
| Loss in 2001 | 1  |
| Loss in 2002 | 2  |
| Loss in 2003 | 3  |
| Loss in 2004 | 4  |
| Loss in 2005 | 5  |
| Loss in 2006 | 6  |
| Loss in 2007 | 7  |
| Loss in 2008 | 8  |
| Loss in 2009 | 9  |
| Loss in 2010 | 10 |
| Loss in 2011 | 11 |
| Loss in 2012 | 12 |
| Loss in 2013 | 13 |
| Loss in 2014 | 14 |

Note that lossyear is zero for pixels that were not forested in 2000, and that the 2013 and 2014 loss layers are not available in the original 2013 Hansen dataset (the 2013 loss layer is available in the 2014 and 2015 updates, while the 2014 loss layer is available in the 2015 update only).

**Band 3 (gain)**

|         |   |
|---------|---|
| No gain | 0 |
| Gain    | 1 |

Note that gain is zero for pixels that were forested in 2000

**Band 4 (lossgain)**

|                  |   |
|------------------|---|
| No loss and gain | 0 |
| Loss and gain    | 1 |

Note that loss and gain is difficult to interpret from the thresholded product, as the original GFC product does not provide information on the sequence (loss then gain, or gain then loss), or the levels of canopy cover reached prior to loss (for gain then loss) or after loss (for loss then gain)

pixels). The layer is calculated here as: `lossgain <- gain & (lossyear != 0)`, where loss year and gain are the original GFC gain and lossyear layers, respectively.

#### Band 5 (datamask)

|         |   |
|---------|---|
| No data | 0 |
| Land    | 1 |
| Water   | 2 |

#### Value

RasterBrick with thresholded GFC product (see details above)

#### See Also

[extract\\_gfc](#)

---

utm\_zone

*Given a spatial object, calculate the UTM zone of the centroid*

---

#### Description

For a line or polygon, the UTM zone of the centroid is given, after reprojecting the object into WGS-84.

#### Usage

```
utm_zone(x, y, proj4string = FALSE)

## S4 method for signature 'numeric,numeric'
utm_zone(x, y, proj4string = FALSE)

## S4 method for signature 'Spatial,missing'
utm_zone(x, proj4string)
```

#### Arguments

|             |  |
|-------------|--|
| x           | a longitude (with western hemisphere longitudes negative), or a Spatial object   |
| y           | a latitude (with southern hemisphere latitudes negative), or missing (if x is a Spatial object)  |
| proj4string | if FALSE (default) return the UTM zone as a string (for example "34S" for UTM Zone 34 South). If TRUE, return a proj4string using the EPSG code as an initialization string. |

#### Details

Based on the code on [gis.stackexchange.com](http://gis.stackexchange.com) at <http://bit.ly/17SdcuN>.

**Examples**

```
utm_zone(45, 10)  
utm_zone(45, -10)  
utm_zone(45, 10, proj4string=TRUE)
```

# Index

`animate_annual`, [2](#), [3](#), [4](#), [9](#)  
`annual_stack`, [2](#), [3](#), [3](#), [7](#), [9](#)

`calc_gfc_tiles`, [4](#)  
`calc_pixel_areas`, [5](#), [10](#)  
`check_aoi`, [5](#)

`dataType`, [10](#)  
`download_tiles`, [6](#), [7](#)

`extract_gfc`, [6](#), [7](#), [8](#), [11](#), [13](#)

`gfc_stats`, [7](#), [8](#)  
`gfc_tiles`, [9](#)

`plot_gfc`, [9](#)

`scale_by_pixel_area`, [10](#)  
`scale_toar`, [10](#)

`test_poly`, [11](#)  
`threshold_gfc`, [3](#), [4](#), [8](#), [11](#)

`utm_zone`, [13](#)  
`utm_zone`, numeric, numeric, logical-method  
    (`utm_zone`), [13](#)  
`utm_zone`, numeric, numeric-method  
    (`utm_zone`), [13](#)  
`utm_zone`, Spatial, missing, logical-method  
    (`utm_zone`), [13](#)  
`utm_zone`, Spatial, missing-method  
    (`utm_zone`), [13](#)

`writeRaster`, [7](#), [11](#)