

# Package ‘maidr’

March 7, 2026

**Type** Package

**Title** Multimodal Access and Interactive Data Representation

**Version** 0.2.0

**URL** <https://github.com/xability/r-maidr>, <https://r.maidr.ai/>

**BugReports** <https://github.com/xability/r-maidr/issues>

**Description** Provides accessible, interactive visualizations through the 'MAIDR' (Multimodal Access and Interactive Data Representation) system. Converts 'ggplot2' and Base R plots into accessible HTML/SVG formats with keyboard navigation, screen reader support, and 'sonification' capabilities. Supports bar charts (simple, grouped, stacked), histograms, line plots, scatter plots, box plots, violin plots, heat maps, density/smooth curves, faceted plots, multi-panel layouts (including patchwork), and multi-layered plot combinations. Enables data exploration for users with visual impairments through multiple sensory modalities. For more details see the 'MAIDR' project <<https://maidr.ai/>>.

**License** GPL (>= 3)

**Encoding** UTF-8

**Imports** base64enc, curl, ggplot2, ggplotify, grid, gridSVG, htmltools, htmlwidgets, jsonlite, shiny, xml2, rlang, R6

**Suggests** testthat (>= 3.0.0), lintr, styler, goodpractice, cyclocomp, knitr, rmarkdown, patchwork

**Config/testthat/edition** 3

**RoxygenNote** 7.3.2

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** JooYoung Seo [aut, cph],  
Niranjan Kalaiselvan [aut, cre]

**Maintainer** Niranjan Kalaiselvan <nk46@illinois.edu>

**Repository** CRAN

**Date/Publication** 2026-03-07 07:40:02 UTC

## Contents

combine_facet_layer_data	2
combine_facet_layer_selectors	3
extract_leaf_plot_layout	3
extract_patchwork_leaves	4
find_children_by_type	4
find_graphics_plot_grob	5
find_panel_grob	5
find_patchwork_panels	6
generate_robust_css_selector	6
generate_robust_selector	7
get_facet_groups	7
maidr_get_fallback	8
maidr_off	9
maidr_on	9
maidr_output	10
maidr_set_fallback	11
map_visual_to_dom_panel	12
organize_facet_grid	12
process_facet_panel	13
process_patchwork_panel	14
render_maidr	14
run_example	15
save_html	16
show	17

<b>Index</b>	<b>19</b>
--------------	-----------

---

combine\_facet\_layer\_data

*Combine data from multiple layers in facet processing*

---

### Description

Combine data from multiple layers in facet processing

### Usage

```
combine_facet_layer_data(layer_results)
```

### Arguments

layer\_results List of layer processing results

### Value

Combined data

---

`combine_facet_layer_selectors`

*Combine selectors from multiple layers in facet processing*

---

**Description**

Combine selectors from multiple layers in facet processing

**Usage**

```
combine_facet_layer_selectors(layer_results)
```

**Arguments**

`layer_results` List of layer processing results

**Value**

Combined selectors

---

`extract_leaf_plot_layout`

*Extract layout from a single leaf ggplot*

---

**Description**

Extract layout from a single leaf ggplot

**Usage**

```
extract_leaf_plot_layout(leaf_plot)
```

**Arguments**

`leaf_plot` The ggplot object

**Value**

Layout with title and axes

extract\_patchwork\_leaves

*Recursively extract leaf ggplots in visual order*

---

### **Description**

Recursively extract leaf ggplots in visual order

### **Usage**

```
extract_patchwork_leaves(node)
```

### **Arguments**

node                    Patchwork node or ggplot object

### **Value**

List of leaf ggplot objects

---

find\_children\_by\_type *Find children matching a type pattern*

---

### **Description**

Find children matching a type pattern

### **Usage**

```
find_children_by_type(parent_grob, pattern)
```

### **Arguments**

parent\_grob            The parent grob to search  
pattern                The pattern to match in grob names

### **Value**

Vector of matching child names

---

`find_graphics_plot_grob`*Utility functions for robust selector generation in Base R plots*

---

**Description**

These functions provide a robust way to find grob elements and generate CSS selectors, independent of panel structure or hardcoded values. Find grob by element type pattern

**Usage**

```
find_graphics_plot_grob(grob, element_type, plot_index = NULL)
```

**Arguments**

<code>grob</code>	The grob tree to search (typically from <code>ggplotify::as.grob()</code> )
<code>element_type</code>	The element type to search for (e.g., "rect", "lines", "points")
<code>plot_index</code>	Optional plot index to match (for multipanel layouts)

**Details**

Searches recursively through a grob tree to find a grob whose name matches the pattern: `graphics-plot-<number>-<element_type>-<number>`

**Value**

The name of the first matching grob, or NULL if not found

---

`find_panel_grob`      *Find the panel grob in a grob tree*

---

**Description**

Find the panel grob in a grob tree

**Usage**

```
find_panel_grob(grob_tree)
```

**Arguments**

<code>grob_tree</code>	The grob tree to search
------------------------	-------------------------

**Value**

The panel grob or NULL if not found

---

`find_patchwork_panels` *Discover panels via gtable layout rows named '^panel-<num>' or '^panel-<row>-<col>' Returns a data.frame with panel\_index, name, t, l, row, col*

---

### Description

Discover panels via gtable layout rows named '^panel-<num>' or '^panel-<row>-<col>' Returns a data.frame with panel\_index, name, t, l, row, col

### Usage

```
find_patchwork_panels(gtable)
```

### Arguments

`gtable`            Gtable object

### Value

Data frame with panel information

---

`generate_robust_css_selector`  
*Generate robust CSS selector from grob name*

---

### Description

Creates a CSS selector that targets SVG elements by their ID pattern, without relying on panel structure or hardcoded values.

### Usage

```
generate_robust_css_selector(grob_name, svg_element)
```

### Arguments

`grob_name`            The name of the grob (e.g., "graphics-plot-1-rect-1")  
`svg_element`        The SVG element type to target (e.g., "rect", "polyline")

### Value

A robust CSS selector string, or NULL if grob\_name is invalid

---

`generate_robust_selector`*Generate robust selector for any element type*

---

**Description**

Creates a robust CSS selector that works regardless of panel structure. This is the main function that layer processors should use.

**Usage**

```
generate_robust_selector(  
  grob,  
  element_type,  
  svg_element,  
  plot_index = NULL,  
  max_elements = NULL  
)
```

**Arguments**

<code>grob</code>	The grob tree to analyze
<code>element_type</code>	The element type to search for (e.g., "rect", "lines")
<code>svg_element</code>	The SVG element to target (e.g., "rect", "polyline")
<code>plot_index</code>	Optional plot index for multipanel layouts
<code>max_elements</code>	Optional limit on number of elements to target

**Value**

A robust CSS selector string, or NULL if element not found

---

`get_facet_groups`*Get facet group information for a panel*

---

**Description**

Get facet group information for a panel

**Usage**

```
get_facet_groups(panel_info, built)
```

**Arguments**

panel_info	Panel information from layout
built	Built plot data

**Value**

List of facet group information

---

maidr\_get\_fallback     *Get Current MAIDR Fallback Settings*

---

**Description**

Retrieves the current fallback configuration for MAIDR.

**Usage**

```
maidr_get_fallback()
```

**Value**

A list with the current fallback settings:

- enabled: Logical indicating if fallback is enabled
- format: Character string of the image format
- warning: Logical indicating if warnings are shown

**See Also**

[maidr\_set\_fallback()] to configure settings

**Examples**

```
# Get current settings
settings <- maidr_get_fallback()
print(settings)
```

---

`maidr_off`*Disable MAIDR Plot Interception*

---

**Description**

Disables automatic MAIDR rendering and restores normal plot behavior. After calling this, Base R plots display in the standard graphics window and ggplot2 objects render with the default ggplot2 method.

**Usage**

```
maidr_off()
```

**Value**

Invisible TRUE on success

**See Also**

[`maidr_on()`] to enable MAIDR rendering

---

`maidr_on`*Enable MAIDR Plot Interception*

---

**Description**

Enables automatic accessible rendering of ggplot2 and Base R plots. In interactive sessions, plots are displayed in the MAIDR interactive viewer. In RMarkdown documents, plots are converted to accessible MAIDR widgets with keyboard navigation and screen reader support.

**Usage**

```
maidr_on()
```

**Value**

Invisible TRUE on success

**See Also**

[`maidr_off()`] to disable MAIDR rendering

## Examples

```
library(maidr)

# Enable interception (on by default after library(maidr))
maidr_on()

# Now all plots render as accessible MAIDR widgets
library(ggplot2)
ggplot(mtcars, aes(x = factor(cyl))) +
  geom_bar()

barplot(table(mtcars$cyl))
```

---

maidr\_output

*MAIDR Output Container for Shiny UI*

---

## Description

Creates a Shiny output container for MAIDR widgets using htmlwidgets. This provides automatic dependency injection and robust JavaScript initialization.

## Usage

```
maidr_output(output_id, width = "100%", height = "400px")
```

## Arguments

output_id	The output variable to read the plot from
width	The width of the plot container (default: "100percent")
height	The height of the plot container (default: "400px")

## Value

A Shiny widget output function for use in UI

## Examples

```
if (interactive()) {
  library(shiny)
  ui <- fluidPage(maidr_output("myplot"))
}
```

---

maidr\_set\_fallback      *Configure MAIDR Fallback Behavior*

---

### Description

Configure how MAIDR handles unsupported plot types or layers. When fallback is enabled, unsupported plots are rendered as static images instead of failing or returning empty data.

### Usage

```
maidr_set_fallback(enabled = TRUE, format = "png", warning = TRUE)
```

### Arguments

enabled	Logical. If TRUE (default), unsupported plots fall back to image rendering. If FALSE, unsupported layers return empty data.
format	Character. Image format for fallback: "png" (default), "svg", or "jpeg".
warning	Logical. If TRUE (default), shows a warning message when falling back to image rendering.

### Value

Invisibly returns a list of the previous settings.

### See Also

[maidr\_get\_fallback()] to retrieve current settings

### Examples

```
# Save current settings and restore on exit
old_settings <- maidr_get_fallback()
on.exit(maidr_set_fallback(
  enabled = old_settings$enabled,
  format = old_settings$format,
  warning = old_settings$warning
))

# Disable fallback (unsupported plots will have empty data)
maidr_set_fallback(enabled = FALSE)

# Use SVG format for fallback images
maidr_set_fallback(format = "svg")

# Disable warning messages
maidr_set_fallback(warning = FALSE)

# Configure multiple options
```

```
maidr_set_fallback(enabled = TRUE, format = "png", warning = TRUE)
```

---

```
map_visual_to_dom_panel
```

*Map visual panel position to DOM panel name*

---

### Description

This function handles the mismatch between visual layout order (row-major) and DOM element generation order (column-major) in gridSVG.

### Usage

```
map_visual_to_dom_panel(panel_info, gtable)
```

### Arguments

panel_info	Panel information from layout
gtable	Gtable object

### Details

Visual layout (row-major): 1 2 3 4

DOM order (column-major): 1 3 2 4

### Value

Gtable panel name or NULL if not found

---

```
organize_facet_grid
```

*Organize subplots into 2D grid structure*

---

### Description

Organize subplots into 2D grid structure

### Usage

```
organize_facet_grid(subplots, panel_layout)
```

### Arguments

subplots	List of processed subplot data
panel_layout	Panel layout information

**Value**

2D grid structure

---

process\_facet\_panel    *Process a single facet panel*

---

**Description**

Process a single facet panel

**Usage**

```
process_facet_panel(
  plot,
  panel_info,
  panel_data,
  facet_groups,
  gtable_panel_name,
  built,
  layout,
  gtable,
  format_config = NULL
)
```

**Arguments**

plot	The original plot
panel_info	Panel information
panel_data	Panel-specific data
facet_groups	Facet group information
gtable_panel_name	Gtable panel name
built	Built plot data
layout	Layout information
gtable	Gtable object
format_config	Optional format configuration from mairr label functions

**Value**

Processed panel data

---

```
process_patchwork_panel
```

*Process a single patchwork panel*

---

### Description

Process a single patchwork panel

### Usage

```
process_patchwork_panel(  
  leaf_plot,  
  panel_name,  
  panel_index,  
  row,  
  col,  
  layout,  
  gtable  
)
```

### Arguments

leaf_plot	The leaf ggplot object
panel_name	Panel name from gtable
panel_index	Panel index
row	Panel row
col	Panel column
layout	Layout information
gtable	Gtable object

### Value

Processed panel data

---

```
render_maidr
```

*Render MAIDR Plot in Shiny Server*

---

### Description

Creates a Shiny render function for MAIDR widgets using htmlwidgets. This provides automatic dependency injection and robust JavaScript initialization.

**Usage**

```
render_maidr(expr, env = parent.frame(), quoted = FALSE)
```

**Arguments**

expr	An expression that returns a ggplot object
env	The environment in which to evaluate expr
quoted	Is expr a quoted expression

**Value**

A Shiny render function for use in server

**Examples**

```
if (interactive()) {
  library(shiny)
  library(ggplot2)
  server <- function(input, output) {
    output$myplot <- render_maidr({
      ggplot(mtcars, aes(x = factor(cyl), y = mpg)) +
        geom_bar(stat = "identity")
    })
  }
}
```

---

run\_example

*Run MAIDR Example Plots*


---

**Description**

Launches example plots demonstrating MAIDR's accessible visualization capabilities. Each example creates an interactive plot using 'show()'.

**Usage**

```
run_example(example = NULL, type = c("ggplot2", "base_r"))
```

**Arguments**

example	Character string specifying which example to run. If 'NULL' (the default), lists all available examples.
type	Character string specifying the plot system to use. Either "ggplot2" (default) or "base_r".

**Details**

Available examples include various plot types such as bar charts, histograms, scatter plots, line plots, boxplots, heatmaps, and more.

Each example script creates a plot and calls ‘show()’ to display it in your default web browser with full MAIDR accessibility features including keyboard navigation and screen reader support.

**Value**

Invisibly returns ‘NULL’. Called for its side effect of displaying an interactive plot in the browser or listing available examples.

**See Also**

[show()] for displaying plots, [save\_html()] for saving to file

**Examples**

```
# List all available examples
run_example()

if (interactive()) {
  # Run ggplot2 bar chart example
  run_example("bar")

  # Run Base R histogram example
  run_example("histogram", type = "base_r")
}
```

---

 save\_html

*Save Interactive Plot as HTML File*


---

**Description**

Save a ggplot2 or Base R plot as a standalone HTML file with interactive MAIDR accessibility features.

**Usage**

```
save_html(plot = NULL, file = "plot.html", ...)
```

**Arguments**

plot	A ggplot2 object or NULL for Base R auto-detection
file	File path where to save the HTML file (e.g., "plot.html")
...	Additional arguments passed to internal functions

**Value**

The file path where the HTML was saved (invisibly)

**Examples**

```
# ggplot2 bar chart
library(ggplot2)
p <- ggplot(mtcars, aes(x = factor(cyl), y = mpg)) +
  geom_bar(stat = "identity")

maidr::save_html(p, tempfile(fileext = ".html"))

# ggplot2 violin plot
p_violin <- ggplot(mtcars, aes(x = factor(cyl), y = mpg)) +
  geom_violin(fill = "lightblue", alpha = 0.7) +
  labs(title = "MPG by Cylinders", x = "Cylinders", y = "MPG")

maidr::save_html(p_violin, tempfile(fileext = ".html"))

# Base R example (requires interactive session for function patching)
if (interactive()) {
  barplot(c(10, 20, 30), names.arg = c("A", "B", "C"))
  maidr::save_html(file = tempfile(fileext = ".html"))
}
```

---

 show

*Display Interactive MAIDR Plot*


---

**Description**

Display a ggplot2 or Base R plot as an interactive, accessible visualization using the MAIDR (Multimodal Access and Interactive Data Representation) system.

**Usage**

```
show(plot = NULL, shiny = FALSE, as_widget = FALSE, ...)
```

**Arguments**

plot	A ggplot2 object or NULL for Base R auto-detection
shiny	If TRUE, returns just the SVG content instead of full HTML document
as_widget	If TRUE, returns an htmlwidget object instead of opening in browser
...	Additional arguments passed to internal functions

**Value**

Invisible NULL. The plot is displayed in RStudio Viewer or browser as a side effect.

**Examples**

```
# ggplot2 bar chart
library(ggplot2)
p <- ggplot(mtcars, aes(x = factor(cyl), y = mpg)) +
  geom_bar(stat = "identity")

maidr::show(p)

# ggplot2 violin plot
p_violin <- ggplot(mtcars, aes(x = factor(cyl), y = mpg)) +
  geom_violin(fill = "lightblue", alpha = 0.7) +
  labs(title = "MPG by Cylinders", x = "Cylinders", y = "MPG")

maidr::show(p_violin)

# Base R example (requires interactive session for function patching)
if (interactive()) {
  barplot(c(10, 20, 30), names.arg = c("A", "B", "C"))
  maidr::show()
}
```

# Index

[combine\\_facet\\_layer\\_data](#), 2  
[combine\\_facet\\_layer\\_selectors](#), 3

[extract\\_leaf\\_plot\\_layout](#), 3  
[extract\\_patchwork\\_leaves](#), 4

[find\\_children\\_by\\_type](#), 4  
[find\\_graphics\\_plot\\_grob](#), 5  
[find\\_panel\\_grob](#), 5  
[find\\_patchwork\\_panels](#), 6

[generate\\_robust\\_css\\_selector](#), 6  
[generate\\_robust\\_selector](#), 7  
[get\\_facet\\_groups](#), 7

[maidr\\_get\\_fallback](#), 8  
[maidr\\_off](#), 9  
[maidr\\_on](#), 9  
[maidr\\_output](#), 10  
[maidr\\_set\\_fallback](#), 11  
[map\\_visual\\_to\\_dom\\_panel](#), 12

[organize\\_facet\\_grid](#), 12

[process\\_facet\\_panel](#), 13  
[process\\_patchwork\\_panel](#), 14

[render\\_maidr](#), 14  
[run\\_example](#), 15

[save\\_html](#), 16  
[show](#), 17